

# 3M™ Head & Face Technical Datasheet



## 3M™ Headgear G500

### Product description

The 3M™ Headgear G500 provides a versatile and comfortable solution for wearers who require both face and hearing protection. With special design features making it easy to combine the headgear with other 3M safety products such as face shields, passive earmuffs or communication headsets and integrated eyewear.

### Key Features:

- Ratchet for size adjustment
- Printable front cover for customized solutions
- Replaceable plastic sweatband
- Compatible with a wide range of 3M™ Peltor™ passive and communications Ear muffs
- Suitable for attaching integrated eyewear V6\*

### Applications

- Gardening
- Forestry

### Size:

The fitting is adjustable between 54 and 62 cm

### Use and storage:

Temperature range for usage: -5°C – +55°C

Recommended storage conditions: -20° C - +55° C, <85% humidity

Recommended maximum shelf life: 5 years.

### Use limitation

- Never modify or alter this product
- Do not use this product against hazards other than those specified
- Refer to the relevant user instruction for further information

### Harness adjustment

8 positions for head size adjustment



### Harness adjustment

Three positions for height adjustment

### Ratchet harness

This solution with its ergonomically designed neck support, makes it possible to obtain maximum comfort for long periods of time. The adjustment dial is made of a TPE-material for enhanced grip

### Frontcover

Ventilation for increased comfort. The frontcover is also designed as a cable holder in combination with Peltor Communication products

### Headband

Robust design ready to be attached to ear muffs



### Integrated eyewear

For additional eye protection, the 3M G500 can incorporate the integrated eye protection range (3M V6\*). Options are available in clear, grey and yellow



V6C Yellow

### Hearing Protection

Thanks to the robust design of the headband, G500 can be used both with and without earmuffs. The slot is 30 mm and fit the Peltor P3E-attachment.

### Mesh Visor

Mesh visors approved for "high speed particles" (45m/s; F) or increased robustness (S) according to EN1731:2006.



# 3M™ Head & Face Technical Datasheet

## Standards and Approval:

The G500 headgear has been shown to meet the basic safety requirements of the European Directive 89/686/EEC and are thus CE marked. The mesh face shield models has been tested in accordance with EN 1731:2006.

The product has been examined by FIOH, Finnish Institute of Occupational Health, Topeliuksenkatu 41 a A, FI-00250, Helsinki, Finland Notified body #0403

Model	European Standard	Symbol	Field of use	Mechanical Strength
G500	EN1731:2006	F	High speed particles	Low energy impact

Model	European Standard	Symbol	Field of use	Mechanical Strength
5B	EN1731:2006	F	High speed particles	Low energy impact (45m/s)
5C-1	EN1731:2006	S	Basic Use	Increased robustness
5J-1	EN1731:2006	S	Basic Use	Increased robustness

If the face shield and the frame are not both marked with the same symbol, the lowest level applies to the complete face protector.

## Technical Specification:

Model	Material(s):	Size	Weight:	Colour:
G500	PP, PA, POM, Stainless steel PVC/Polyester	-	212 g (w/o face shield)	black/orange

The headgear can carry both mesh face shields as well as clear face shields.

## Available Mesh face shields:

Model	Material(s):	Size	Light reduction	Weight:	Colour:
5B	Polyamide mesh	ø 0,3 1,0 x 1,0 mm	45%	45 g	Black
5C-1	Stainless steel mesh	ø 0,24 1,8 x 2,5 mm	24%	54 g	Black
5J-1	Etched stainless steel mesh	Area 1: 4,0x1,5x0,15 mm Area 2: 3,8x1,4x0,15 mm Area 3: 3,7x1,3x0,15 mm	Area 1: 17% Area 2: 28% Area 3: 37%	53 g	Black

For polycarbonate face shields see specific Technical data sheet

## Spare Parts and Accessories:

Product code	Description
5B	Face shield, Polyamide mesh
5C-1	Face shield, Stainless steel mesh
5J-1	Face shield, Stainless steel mesh, etched
V6C	Integrated safety eyewear, Yellow
V6B	Integrated safety eyewear, Grey
V6E	Integrated safety eyewear, Clear
HYG50	Plastic sweat band

## Important Notice

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



3M Deutschland GmbH  
Carl-Schurz-Straße 1  
41453 Neuss  
Tel.: +49 (0) 2131 14 26 04  
Fax: +49 (0) 2131 14 32 00  
E-Mail: arbeitsschutz.de@mmm.com  
Web: www.3Marbeitsschutz.de

3M (Schweiz) GmbH  
Eggstrasse 93  
8803 Rüslikon  
Tel.: +41 (0) 44 724 91 51  
Fax: +41 (0) 44 724 94 40  
E-Mail: arbeitsschutz-ch@mmm.com  
Web: www.3Marbeitsschutz.ch

3M Österreich GmbH  
Kranichberggasse 4  
1120 Wien  
Tel.: +43 (0) 1 86 686 541  
Fax: +43 (0) 1 86 686 229  
E-Mail: arbeitsschutz-at@mmm.com  
Web: www.3Marbeitsschutz.at